

# **RADIO SPACER BIN**

## **DESCRIPTION**

### **BACKGROUND OF THE INVENTION**

**[Para 1] 1. Field of the Invention**

**[Para 2]** The present invention generally relates to a vehicle interior and, more particularly, to spacer bin that provides for mounting a standard radio within a instrument panel cavity designed for the larger sized radio having a navigation screen.

**[Para 3] 2. Description of the Related Art**

**[Para 4]** With ever-increasing pressure from automotive consumers, flexibility and adaptability of vehicle interiors is increasingly required in order to provide a vehicle that meets broad customer demands. Further, with the greater number of components available for installation within the instrument panel there is increasing pressure from manufacturers to provide the needed flexibility while simplifying the assembly line procedures and reducing parts inventory and costs.

**[Para 5]** For example, U.S. Patent Number 5,873,749 issued February 23, 1999 to Takiguchi et al. teaches an electrical component mounting opening in an instrument panel unit having an electrical connection means as well as physical attachment means incorporated within said electrical component mounting opening.

**[Para 6]** U.S. Patent Number 6,517,145 issued February 11, 2003 to Hedderly teaches a cast magnesium instrument panel structure which may be cast as a single unit or as multiple mating units.

[Para 7] U.S. Patent Number 6,709,041 issued March 23, 2004 to Hotary et al. teaches a center consol adaptable to receive various components within pre-sized component mounting openings.

## DISCLOSURE OF THE INVENTION

[Para 8] The present invention provides advantages and alternatives over the prior art by providing a radio spacer bin that allows for a single bracket in the instrument panel to accept the mounting of either a larger style radio unit or a smaller standard radio unit.

[Para 9] According to a further aspect of the present invention, there is provided a radio bin spacer allowing for the mounting of a standard sized radio in a mounting area designed for the larger style radio comprising: a bin having one closed end and one open end and further having a top wall, a bottom wall and two side walls; said top wall having a structural rib located thereon; said side walls each having a mounting tab located thereon wherein each said mounting tab has a bore located therein; and the rear end of said bin having a pair of spacer stanchions located thereon; thereby providing a mounting area sized for a standard radio in a larger radio sized opening in an instrument panel.

[Para 10] According to yet another aspect of the present invention a radio bin spacer allowing for the mounting of a standard sized radio in a mounting area designed for the larger larger style radio comprising: a bin having one closed end and one open end and further having a top wall, a bottom wall and two side walls; said top wall having a structural rib located thereon; said side walls each having a mounting tab located thereon wherein each said mounting tab has a bore located therein; structural ribs located on said side walls adjacent to said mounting tabs; and the rear end of said bin having a pair of spacer stanchions located thereon; thereby providing a mounting area sized for a standard radio in a larger radio sized opening in an instrument panel.

[Para 11] The present invention thus advantageously provides a for flexibility of radio options to the consumer while reducing the number of brackets and their cost to the manufacturer as well as simplifying the line assembly procedures.

## BRIEF DESCRIPTION OF THE DRAWINGS

[Para 12] Figure 1 shows a perspective front view of the radio bin spacer of the present invention.

[Para 13] Figure 2 shows a perspective partial section rear view of a instrument panel mounting bracket holding a component and the radio bin spacer of the present invention.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS OF THE INVENTION

[Para 14] Reference will now be made to the drawings, wherein to the extent possible like reference numerals are utilized to designate like components throughout the various views. Referring to Figure 1, which presents a radio bin spacer 10 of the present invention comprising a bin having an open front end 1, a closed rear end 2 (Figure 2) and four walls 3.

[Para 15] As further shown in Figure 1, radio bin spacer 10 has located on each rear corner a spacer stanchion 4, a structural rib 5 located on the top sidewall 3, and a pair of mounting tabs 6, each said tab 6 having a bore 7 for fixedly mounting said radio bin spacer 10 to an instrument panel mounting bracket 20.

[Para 16] As also shown in Figure 1, are optional bin front structural ribs 8 located sidewalls 3 on each side of tabs 6.

[Para 17] Referring now to Figure 2, there is shown rear perspective view of an instrument panel mounting bracket 20 holding a component 30 as well as the radio bin spacer 10 of the present invention. The radio bin spacer 10 is shown with rear end 2 and spacer stanchions 4 as well as mounting tab 6 having bore 7 and optional bin front structural ribs 8 located on walls 3

[Para 18] As previously set forth, the present invention allows for a single instrument panel mounting bracket 20 to be used to mount either a larger style radio or the smaller sized standard style radio within the instrument panel without the need for separate instrument mounting brackets being installed depending on the radio option ordered.

[Para 19] The presently preferred radio bin spacer 10 comprises an injection molded plastic construction. The preferred plastics for injection molding the radio bin spacer 10 of the present invention include, for example, polypropylene, thermoplastic olefins (TPO), acrylonitrile butadiene styrene (ABS), and polycarbonates. Presently preferred is polypropylene. It is to be understood that the present invention may be manufactured using other methods and materials which are well known in the art, such as for example, magnesium casting, and the like.

[Para 20] It is also contemplated that the present invention may be utilized in an instrument panel that incorporates larger style radio mounting features that do not require a separate mounting bracket.

[Para 21] Although the preferred embodiments of the present invention has been disclosed, various changes and modifications may be made without departing from the scope of the invention as set forth in the appended claims.

